



15005 BKT

15005 AZT

15005 MST

## THREE TIER

Louvers direct tiers of light downwards for well-shielded, dramatic lighting. Blends nicely with shrubs or flowers along a pathway. Available in stem or deck mount or as a bollard.

## SPECIFICATIONS

**Housing** Durable die-cast aluminum construction. Molded ribbed diffuser of clear UV stabilized high impact resistant polycarbonate. *Mounting stems and bollard kits sold separately.*

**Finish** Textured Architectural Bronze, Textured Black, Textured Midnight Spruce™

**Wiring** 52" of usable #18-2, SPT-1-W leads. Cable connector supplied with 12-Volt fixture. S-8 wedge socket.

**Light Bulb** 24.4-W. Max. 3156K (15598CLR) (nominal at 12-Volts) supplied. Can also use 18.5-W. 3155K (15599CLR).


### Optional Mounting Accessories

- 15656, 15657, 15658 or 15570 – Stems
- 15575 BK, 15576 BK or 15578 – Stakes
- 15665, 15666 or 15667 – Bollard
- 15671 ST – Bollard Template Kit
- 15601 – Surface Mounting Flange
- 15602 – Flange Mounting Nipple
- 15607 – Tree/Surface Mounting Bracket

U.S. Patent No. Des. 330,603

Canada Patent No. 69176

Korea Design Registration Number 126685



Footcandle/Distance from Fixture Center

Stem Height	1'	2'	3'	4'	5'	6'	7'	8'	9'
12"	2.1	.93	.67	.18	-	-	-	-	-
*18"	1.8	.73	.4	.27	.03	-	-	-	-
24"	1.2	.67	.33	.35	.27	.15	-	-	-

Light Bulb Conversion: 18.5W, 3155K Light Bulb, FCx66