

# KICHLER®


## Medium Landscape Accent



PROJECT:
TYPE:
ORDERING # :
COMMENTS:






## FEATURES

- 5" Accent Light For Cross-Lighting, Accenting, or Grazing
- Cast Aluminum Housing
- Tempered Convex Glass Lens
- 8" of Usable 200° 18 AWG Wire Leads
- 4000V (4KV) Pulse Rated Medium Base Porcelain Socket
- Max Lamping 70W PAR30L Metal Halide or 75W PAR30L / R30 Incandescent (Not Included)
- Remote Ballast Required for HID Lamping
- ANSI / UL Listed Wet Location
- Housing Includes a 1-Year Warranty From Date of Purchase
- HID Ballasts Include a 2-Year Warranty From Date of Purchase



## ORDERING INFORMATION

EXAMPLE: 15241AZT (Product # & Finish)

PRODUCT	FINISH	REMOTE BALLAST SPECS	MOUNTING ACCESSORIES	LENS ACCESSORIES
15241	AZT - Textured Architectural Bronze	<p><b>Above Ground Ballast</b></p> <p><b>15MH570AZT</b> - Single 70W MH 120V ANSI M98</p> <ul style="list-style-type: none"> <li>- Dimensions: 6.375" W x 9.5" L x 5.25" D</li> <li>- Stamped Steel w/ Textured Architectural Bronze Thermoset Powder Coat Finish</li> <li>- Copper Wrapped Core &amp; Coil w/ HPF 105° High Heat Capacitor</li> <li>- Long Range Ignitor</li> <li>- Rated For -20° F Starting</li> <li>- 0.5" &amp; 0.75" Trade Size Combination Knockouts For Conduit Entry</li> <li>- Mounting Screws &amp; Anchors Included</li> <li>- UL Listed For US &amp; Canada</li> </ul> 	 <p>4.375" 19" 2.25"</p>	<p><b>15640AZT</b> - PAR30 / R30 Medium Cowl - 3.87" in Length</p> <p><b>15640BKT</b> - PAR30 / R30 Medium Cowl - 3.87" in Length</p>  <p><b>15648BKT</b> - PAR30 / R30 Long Cowl - 8.99" in Length</p> <p><b>15648BL</b> - PAR30 / R30 Long Cowl - 8.99" in Length</p> 
	BKT - Textured Black	<p><b>In Ground Ballast</b></p> <p><b>15IGMHS70AZ</b> - Single 70W MH 120V ANSI M98</p> <ul style="list-style-type: none"> <li>- Dimensions: 9.625" Diameter x 12" Height</li> <li>- Single Piece Polyphenylene (PPS) Glass Reinforced Composite w/ Molded-in Ribs to Prevent Ground Shift</li> <li>- Quick Disconnect Ballast w/ Bracket Handle</li> <li>- 0.5" NPSM Removable Plug For Direct Fixture Mount &amp; Remote Mount Application</li> <li>- Two Threaded 0.75" NPT Entries For Conduit Attachment</li> <li>- Re-Enterable Encapsulant 3M 8882 Potting Compound Included</li> <li>- One Piece, Molded Silicone O-Ring</li> <li>- Captive &amp; Gasketed</li> <li>- CSA Listed For US &amp; Canada</li> </ul>  <p><b>Please Note:</b> Maximum Distance From Lamp to Ballast Cannot Exceed 15 Feet</p>		

## NOTES

For Warranty Information, please visit [www.landscapelighting.com](http://www.landscapelighting.com)

We reserve the right to revise the design or components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.

