



15326 AZT
15926 AZT



15326 BE



15326 BKT



15326 MST

CENTER MOUNT

Unobtrusive, center-mount fixture for maximum light spread.

SPECIFICATIONS

Housing Durable die-cast aluminum construction

Finish Textured Architectural Bronze, Textured Black, Beach, Textured Midnight Spruce™

Wiring 35" of usable #18-2, SPT-1-W leads. Cable connector supplied with fixture. 12-Volt S-8 wedge socket.

Light Bulb 24.4-W. Max. 3156K (15598CLR) (nominal at 12-Volts) supplied. Can also use 18.5-W. 3155K (15599CLR).


Mounting Accessories Included
18" stem* and 8" In-ground stake

Optional Mounting Accessories
15601 – Surface Mounting Flange
15607 – Tree/Surface Mounting Bracket

Bulk Pack 15326AZT6 includes 6 fixtures and 6 (8") In-ground stakes

Bulk Pack Pre-Wired With Universal Connector
15926AZT6 with 25' of 16 gauge cable lead for use with Pro Series LV Junction

U.S. Patent No. Des. 330,603
Canada Patent No. 69176
Korea Design Registration Number 126685



Footcandles/Distance from Fixture Center

Stem Height	1'	2'	3'	4'	5'	6'	7'	8'	9'
12"	21.8	5.3	1.5	.1	-	-	-	-	-
18"	16.6	6.3	2.2	.87	.1	-	-	-	-
24"	7.9	6.1	2.7	1.2	.55	.2	-	-	-

Light Bulb Conversion: 18.5W, 3155K Light Bulb, FC66