



**15073 AZT**



**15074 AZT**

## BRICK LIGHT

Designed to be integrated into brick walls during construction. Casts a low, even spread of light. Available with or without louvers.

### SPECIFICATIONS

**Housing** Die-cast aluminum with a fully sealed heat-resistant glass lens

**Finish** Textured Architectural Bronze


**Wiring** Wire connection must be made inside junction box. 12-Volt bi-pin, high temperature porcelain socket.

**Light Bulb** (2) 10-W. Max. Q10T3 (15571CLR) halogen (nominal at 12-Volts) supplied. 75° supply wire required.

Masonry or Concrete use only



**15073**  
Louver face



**15074**  
Heat-resistant glass lens

**15073 – Footcandles/Distance from Fixture Center**

Mounting Height	.5'	1'	1.5'	2'	2.5'	3'	3.5'	4'	4.5'	5'
12"	.3	1.1	.8	.5	.1	.02	-	-	-	-
24"	-	-	.1	.2	.2	.2	.1	.03	.02	-
36"	-	-	-	-	.01	.01	.03	.06	.03	.01

**15074 – Footcandles/Distance from Fixture Center**

Mounting Height	.5'	1'	1.5'	2'	2.5'	3'	3.5'	4'
12"	-	-	-	-	.01	.04	.04	-
24"	-	-	.06	.1	.09	.04	.04	-
36"	-	.02	.04	.04	.04	.04	.04	.01